

Name: _____ Date: _____

Company: _____

Shipping Address: _____

City: _____ State: _____ Zip: _____

Work Phone: _____ Fax: _____ Mobile: _____

Customer Number: _____ Email: _____

- Shipping: FEDEX GROUND FEDEX NEXT DAY FEDEX 2-DAY
 UPS GROUND UPS NEXT DAY UPS 2 -DAY UPS 3-DAY
 OTHER/NOTES: _____

Orders Cannot Be Acknowledged or Shipped Without a Valid Fax Number. All Orders Must Be Faxed. Verbal Orders are the responsibility of the Purchaser. No Refunds or Exchanges.

Quantity:	Overall Length	Over Ball Length	Under Ball Length
Quantity:	Overall Length	Over Ball Length	Under Ball Length
Quantity:	Overall Length	Over Ball Length	Under Ball Length
Quantity:	Overall Length	Over Ball Length	Under Ball Length
SPECIAL INSTRUCTIONS:			

- Diameter/ Wall 5/16"/.105" Wall 3/8"/.135" Wall
 7/16"/.165" Wall 1/2"/.200" Wall
 9/16"/.187" Wall 5/8"/.125" Wall
 5/8"/.188" Wall H-13 Solid

- Rocker End 5/16" Ball 3/8" Ball
 .281 Radius Cup .281 Radius Cup BZ
 5/16" Cup 3/8" Cup

- Lifter End 5/16" Ball 3/8" Ball
 Oil Restrictor (not available on all pushrods)

- Options Full Taper Double Taper
 Half Taper Neck Down

- Tip 5/8" Rocker Tip 5/8" Lifter Tip
 1-5/8" Lifter Tip Length 1-5/8" Rocker Tip Length
 Full Taper Double Taper, 1-5/8" Clearance

Standard Ball End Tips are 1- 5/8" With 210° Clearance

